Revelite AL SKU Builder

| NAME OF ARTWORK | CANVAS HEIGHT CANVAS WIDTH_ | | (canvas or desired illuminated area) | | |
|--|---|---|--------------------------------------|--|--|
| CLIENT/PROJECT | DATE | | | | |
| | REVE | LITE AL PART #AL | | | |
| CANVAS HEIGHT | | | | | |
| | | | | | |
| Height | Height less than 16" Height 16" or greater | 1 2 | | | |
| CANVAS WIDTH NOMINAL WIDTHS | | | | | |
| 7 10 12 14 17 19 22 24 | 26 29 31 34 36 38 41 43 46 48 | 50 53 55 58 60 | | | |
| If the actual width is between two no If the canvas is over 60" wide, two of The horizontal light distribution may joined. Leave this section blank and | the actual width of the canvas (or desired illustiminal widths, we recommend choosing the stormore fixtures will be used side by side any appear disrupted beneath the point at whice we will select the appropriate fixtures for you section is filled out at the top of this form.) | maller nominal width. d joined by a bracket. th the two fixtures are | | | |
| REVELITE AL FINISHES | | | | | |
| | | GD W | | | |
| GD W BL A BZ | BB SN | BL A | | | |
| Gold White Black Brushed Oil Rubbed | Brushed Satin Nickel | BZ | | | |
| STANDARD Bronze | PREMIUM | BB SN | | | |
| PROFILE SHAPES | | | | | |
| | Low Profile Round | L | | | |
| Low Profile Round MOUNTING METHOD | | | | | |
| | | - 1 | | | |
| Standard Mount The standard mount can be attached to | Standard Mounting Direct Wire Wall Mount Square Co | anopy D | | | |
| the frame of the painting or to the wall. | Direct Wire Wall Mount Rectangle | ' / | | | |
| Direct Wire Wall Mount The direct wire wall mount attaches directly to the J-box* | *The direct wire wall mount is available in two differ Square: 4.5"W x 4.5"H Rectangle: 4.5"W x 3"H The rectangular option must use a single gang J-b A plug-in power supply is not available for the Direct | ox mounted horizontally. | | | |
| POWER | | | | | |
| The Revelite AL is a low voltage fixture and must be used | Plug-In (Only Available with Stan | dard Mount) P | | | |
| with an approved power supply. | Hardwired | н — | | | |
| Plug-In Hardwired | No Power Supply* *Only choose the "No Power Supply" option if you he manufacturer and discussed a custom power supply. | | | | |
| COLOR TEMPERATURE | | | | | |
| 27 30 | | 27 | | | |
| 2700 K LED 3000 K LED | | 30 | | | |